

ACCESSORIES – ALL MODELS

INDEX	PRODUCT NAME	DESCRIPTION
MGL1	External cable bushing (cover)	<ul style="list-style-type: none"> • length 300 mm • made out of stainless steel, heads out of anodized aluminum • loop diameter: internal 9,8 mm, external 12 mm
MGL2	External cable bushing (cover)	<ul style="list-style-type: none"> • length 500 mm • made out of stainless steel, heads out of anodized aluminum • loop diameter: internal 9,8 mm, external 12 mm
MG300.T	Universal timer	<ul style="list-style-type: none"> • electronic delay of locking/unlocking • used for electrin strikes and electro-magnets Hartte • possibility to adjust delay time from 0 to 90 seconds • voltage 12/24 V DC • power consumption 0,1 mA, max current 1,5A (max 30V DC) • starting at power on or on trigger
CON.AC	Converter DC/AC	<ul style="list-style-type: none"> • enable change from direct current into alternating current • improve preload force parameter for electric strikes powered by direct current (DC)
CON.24	Converter of power 12V -> 24V	<ul style="list-style-type: none"> • enable change from 12V into 24V

ACCESSORIES – ALL MODELS

INDEX	PRODUCT NAME	DESCRIPTION
CON.12	Converter 24V -> 12V	<ul style="list-style-type: none"> ● enable change from 24V into 12V
ALR-S	Additional Lock to steel doors	<ul style="list-style-type: none"> ● to steel doors ● mechanical lock with adjustable latch ● adjustable latch – depth of latch adjustable from 0mm to 16mm ● symmetric housing, 2 assembly holes ● designed to DIN-left and DIN-right doors ● dimensions 18 x 63 x 37 mm ● dimensions of lock with plate: 24 (width) x 110 x 40 mm
ALR-A	Additional Lock to aluminium doors	<ul style="list-style-type: none"> ● to aluminium doors ● mechanical lock with adjustable latch ● adjustable latch – depth of latch adjustable from 0mm to 16mm ● symmetric housing, 2 assembly holes ● designed to DIN-left and DIN-right doors ● dimensions 18 x 63 x 37 mm ● dimensions of lock with plate: 20 (width) x 110 x 40 mm
ALR-W	Additional Lock to wooden doors	<ul style="list-style-type: none"> ● to wooden doors ● mechanical lock with adjustable latch ● adjustable latch – depth of latch adjustable from 0mm to 16mm ● symmetric housing, 2 assembly holes ● designed to DIN-left and DIN-right doors ● dimensions 18 x 63 x 37 mm ● dimensions of lock with plate: 24 (width) x 110 x 40 mm
ALR-WN	Additional Lock to wooden narrow doors	<ul style="list-style-type: none"> ● to wooden narrow doors ● mechanical lock with adjustable latch ● adjustable latch – depth of latch adjustable from 0mm to 16mm ● symmetric housing, 2 assembly holes ● designed to DIN-left and DIN-right doors ● dimensions 18 x 63 x 37 mm ● dimensions of lock with plate: 20 (width) x 110 x 40 mm

ACCESSORIES – ALL MODELS

INDEX	PRODUCT NAME	DESCRIPTION
Standard reed magnetic detector	Standard reed magnetic detector	<ul style="list-style-type: none">• mortise mounting• NC• gap 19mm, diameter 10mm, length 32mm• polycarbonate casing in white colour
Extractor	Additional, suitable element pushing out cabinet door, when unlocking.	<ul style="list-style-type: none">• surface mounting• plastic housing